

Fire Extinguisher Series

ABC Dry Powder Fire Extinguisher

Feature: ABC Dry Powder Extinguisher is suitable for fire on ordinary combustible, highly inflammable liquids, gases expelled under pressure and fires under electric

Specification

Model	Filled Weight (Kg)	Volume (L)	Working Pressure (Mpa)	Discharge Range (m)	Discharge Time (S)	Fire Rating	Operating Temperature (°C)	Material	Packing Size (cm)	Quantity /Case
MFZL1	1±0.05	1.1	1.2	≥3.0	≥8	1A,2B	-20℃~+55℃	08AL	40X30X33	12
MFZL2	2±0.06	2.35	1.2	≥3.0	≥8	1A,3B	-20℃~+55℃	08AL	34X24X39	6
MFZL3	3±0.08	4.16	1.2	≥3.0	≥13	2A,5B	-20℃~+55℃	08AL	29X29X46.5	4
MFZL4	4±0.08	4.69	1.2	≥3.0	≥13	2A,9B	-20℃~+55℃	08AL	30X30X52	4
MFZL5	5±0.10	6.1	1.2	≥3.5	≥13	3A,14B	-20℃~+55℃	08AL	31X16.5X56	2
MFZL8	8±0.16	9.38	1.2	≥5.0	≥14	4A,22B	-20℃~+55℃	08AL	36X18X58	2



BC Dry Powder Fire Extinguisher

Feature: BC Dry Powder Extinguisher is suitable for highly inflammable liquids, gases expelled under pressure and fires under electric tension.

Specification

Model	Filled Weight (Kg)	Volume (L)	Working Pressure (Mpa)	Discharge Range (m)	Discharge Time (S)	Fire Rating	Operating Temperature (°C)	Material	Packing Size (cm)	Quantity /Case
MFZ1	1±0.05	1.1	1.2	≥3.0	≥8	1A,2B	-20℃~+55℃	08AL	40X30X33	12
MFZ2	2±0.06	2.35	1.2	≥3.0	≥8	1A,3B	-20℃~+55℃	08AL	34X24X39	6
MFZ3	3±0.08	4.16	1.2	≥3.0	≥13	2A,5B	-20℃~+55℃	08AL	29X29X46.5	4
MFZ4	4±0.08	4.69	1.2	≥3.0	≥13	2A,9B	-20℃~+55℃	08AL	30X30X52	4
MFZ5	5±0.10	6.1	1.2	≥3.5	≥13	3A,14B	-20℃~+55℃	08AL	31X16.5X56	2
MFZ8	8±0.16	9.38	1.2	≥5.0	≥14	4A,22B	-20℃~+55℃	08AL	36X18X58	2



CO₂ Fire Extinguisher

Feature: CO₂ Fire Extinguisher is suitable for smothering fires on oils, greases, flammable liquids & gases, electric appliances, instruments, mechanical equipments, etc. at the initial stage.

Specification

Model	Filled Weight (Kg)	Volume (L)	Discharge Range (m)	Discharge Time (S)	Fire Rating	Operating Temperature (°C)	Material	Packing Size (cm)	Quantity /Case
MT2	2.1	3	≥2.0	≥8	2B	-10℃~+55℃	CK45	37X30X14	2
MT3	3.1	4.5	≥2.0	≥8	3B	-10℃~+55℃	CK45	46X30X14	2
MT5	5.1	7.5	≥2.5	≥8	4B	-10℃~+55℃	CK45	70X22X16	1
MT7	7.1	10.5	≥2.5	≥8	5B	-10℃~+55℃	CK45	75.5X21.5X16	1

