



Powder

Extinguishers

Model	A	B	C	D	F
PD 1	8 A	34 B			
PD 2	13 A	70 B			
PD 4	21 A	113 B			
PD 6	34 A	183 B			
PD 9	43 A	233 B			
PD 12	55 A	233 B			
PD 6 MAX	34 A	233 B			

Product description

SFFECO Dry Powder extinguishers are characterised by their high performance, simple method of operation and rapid fire knock down capability. They are suitable for tackling fires involving freely burning materials, petrol & oils, gas & electrical equipment. They are ideal for vehicle & marine risks. SFFECO powder extinguishers contain high performance powder and are one of the most powerful powder extinguishers in the world.

Features:

- Monoammonium Phosphate based Dry Chemical agent. Capable of fighting class A, B, C & E Fires.
- Kite Mark Certified to BS EN3
- High Quality Polyester Powder Coated Paint
- Controlled Discharge
- Brass Nickel Plated Head Valve with simple squeeze operation.
- Unique gauge testing system
- Unique colour coded handle and base (Optional)
- Rechargeable and easy to service
- Choice of capacity from 1 to 12 Kg.

Ideal Use : Homes, Office, Buildings warehouses, Farms and Wood working area etc.

Note: Not recommended for use on expensive and delicate equipments like computer etc.



MODEL	PD1	PD2	PD4	PD6	PD9	PD12
Capacity	1 Kg.	2 Kg	4 Kg	6 Kg	9 Kg	12 Kg
Fire Rating	8A 34B	13A 70B	21A 113B	34A 183B	43A 233B	55A 233B
Average discharge time	9.0 sec	14.0 sec	18.0 sec	21 sec	23 sec	32 sec
Height without base	340mm	385mm	410mm	515mm	525mm	620mm
Diameter	78mm	111mm	150mm	150mm	185mm	185mm
Filled weight	1.92 kg	3.5 kg	7.1kg	10 kg	14 kg	17.9 kg
Empty weight	0.92 kg	1.5 kg	3.1 kg	4 kg	5 kg	5.9 kg
Operating temperature	-20°C to 60°C					
Working Pressure at 20°C	14 bar	14 bar	15 bar	15 bar	15 bar	15 bar
Maximum Service Pressure	17.9 bar	16.6 bar	15.9 bar	15.9 bar	16.4 bar	16.7 bar
Test Pressure	30 bar	30 bar	30 bar	30 bar	30 bar	30 bar

